

## CLAIMS

1 (cancelled).

1 2 (cancelled).

1 3 (cancelled).

1 4 (cancelled).

1 5 (cancelled).

1 6 (cancelled).

1 7 (cancelled).

1 8 (cancelled).

1 9 (cancelled).

1 10 (cancelled).

1 11 (cancelled).

1 12 (cancelled).

1 13 (cancelled).

1 14 (cancelled).

1 15 (cancelled).

1 16 (previously presented). A decorative cabinet door assembly made of wood  
2 and comprising:

3 a generally rectangular frame including an upper frame member, a  
4 lower frame member, a pair of opposing side members and an open space  
5 defined between said upper frame member, said lower frame member and said  
6 pair of opposing side members, said opposing side members each having a  
7 narrow slot in an inner edge thereof and one of said upper and lower frame

8 members having a slot extending between an inner edge and an outer edge  
9 thereof, with a groove along said outer edge communicating in parallel relation  
10 with said slot, and the other of said upper frame member and said lower frame  
11 member having a recess along an inner side thereof, and opposed notches at  
12 lower outer regions of said recess, said slot, each said narrow slot and an inner  
13 surface of said recess all being coplanar;

14 a decorative changeable, flexible, fabric sheet panel slightly wider  
15 than said open space and having a first tubular loop contiguous with and  
16 formed at one end of said fabric sheet panel and a second tubular loop  
17 contiguous with and formed at the other end of said fabric sheet panel, said  
18 first tubular loop and said second tubular loop extending an entire width of  
19 said fabric sheet panel, one of said first tubular loop and said second tubular  
20 loop removably extending straight through said slot and resides in said groove  
21 in said one of said upper frame member and said lower frame member, said  
22 flexible sheet panel also extending straight into said recess, said recess being  
23 generally of a width of said fabric sheet panel, said fabric sheet panel further  
24 extending unsupported along each side into each said narrow slot of each of  
25 said opposed side members,

26 a first dowel pin inserted through the loop that extends through said  
27 slot, said first dowel pin positioned in said groove, thereby securing said fabric  
28 sheet panel in place in said one of said upper frame member and said lower  
29 frame member,

30 a second dowel pin slightly longer than the other of said first loop and

31 said second loop and inserted through the other of said first loop and said  
32 second loop, with ends of said second dowel pin engaging said opposed notches  
33 of said recess, thereby securing said fabric sheet panel in said recess and  
34 tensioning said fabric sheet panel between said upper frame member and said  
35 lower frame member,

36 wherein said flexible sheet panel is supported and stretched between  
37 said outer edge of said one of said upper frame member and said lower frame  
38 member and an opposed said one of said upper frame member and said lower  
39 frame member.

1 17 (previously presented). A decorative cabinet door assembly comprising:

2 a generally rectangular frame including an upper frame member, a  
3 lower frame member, a pair of opposing side members and an open space  
4 defined between said upper frame member, said lower frame member and said  
5 pair of opposing side members, said opposing side members each having a  
6 narrow slot in an inner edge thereof and one of said upper and lower frame  
7 members having a slot extending between an inner edge and an outer edge  
8 thereof, with a groove along said outer edge communicating in parallel relation  
9 with said slot, and the other of said upper frame member and said lower frame  
10 member having a recess along an inner side thereof, and opposed notches at  
11 lower outer regions of said recess, said slot, each said narrow slot and an inner  
12 surface of said recess all being coplanar;

13 a decorative changeable, flexible, fabric sheet panel slightly wider

14 than said open space and having a first tubular loop contiguous with and  
15 formed at one end of said fabric sheet panel and a second tubular loop  
16 contiguous with and formed at the other end of said fabric sheet panel, said  
17 first tubular loop and said second tubular loop extending an entire width of  
18 said fabric sheet panel, one of said first tubular loop and said second tubular  
19 loop removably extending straight through said slot and resides in said groove  
20 in said one of said upper frame member and said lower frame member, said  
21 flexible sheet panel also extending straight into said recess, said recess being  
22 generally of a width of said fabric sheet panel, said fabric sheet panel extending  
23 into each said narrow slot of each of said opposed side members,

24 a first dowel pin inserted through the loop that extends through said  
25 slot, said first dowel pin positioned in said groove, thereby securing said fabric  
26 sheet panel in place in said one of said upper frame member and said lower  
27 frame member,

28 a second dowel pin slightly longer than the other of said first loop and  
29 said second loop and inserted through the other of said first loop and said  
30 second loop, with ends of said second dowel pin engaging said opposed notches  
31 of said recess, thereby securing said fabric sheet panel in said recess and  
32 tensioning said fabric sheet panel between said upper frame member and said  
33 lower frame member,

34 wherein said flexible sheet panel is supported and stretched between  
35 said outer edge of said one of said upper frame member and said lower frame  
36 member and an opposed said one of said upper frame member and said lower

37 frame member.

1 18 (previously presented). A decorative cabinet door assembly comprising:

2 a generally rectangular frame including an upper frame member, a  
3 lower frame member, a pair of opposing side members and an open space  
4 defined between said upper frame member, said lower frame member and said  
5 pair of opposing side members, said opposing side members each having a  
6 narrow slot in an inner edge thereof and one of said upper and lower frame  
7 members having a slot extending between an inner edge and an outer edge  
8 thereof, with a groove along said outer edge communicating in parallel relation  
9 with said slot, and the other of said upper frame member and said lower frame  
10 member having a recess along an inner side thereof, and opposed notches at  
11 lower outer regions of said recess, said slot, each said narrow slot and an inner  
12 surface of said recess all being coplanar;

13 a decorative changeable, flexible, fabric sheet panel slightly wider  
14 than said open space and having a first tubular loop contiguous with and  
15 formed at one end of said fabric sheet panel and a second tubular loop  
16 contiguous with and formed at the other end of said fabric sheet panel, said  
17 first tubular loop and said second tubular loop extending an entire width of  
18 said fabric sheet panel, one of said first tubular loop and said second tubular  
19 loop removably extending straight through said slot and resides in said groove  
20 in said one of said upper frame member and said lower frame member, said  
21 flexible sheet panel also extending straight into said recess, said recess being

22 generally of a width of said fabric sheet panel, said fabric sheet panel further  
23 extending unsupported along each side into each said narrow slot of each of  
24 said opposed side members,

25 a first dowel pin inserted through the loop that extends through said  
26 slot, said first dowel pin positioned in said groove, thereby securing said fabric  
27 sheet panel in place in said one of said upper frame member and said lower  
28 frame member,

29 a second dowel pin slightly longer than the other of said first loop and  
30 said second loop and inserted through the other of said first loop and said  
31 second loop, with ends of said second dowel pin engaging said opposed notches  
32 of said recess, thereby securing said fabric sheet panel in said recess and  
33 tensioning said fabric sheet panel between said upper frame member and said  
34 lower frame member,

35 wherein said flexible sheet panel is supported and stretched between  
36 said outer edge of said one of said upper frame member and said lower frame  
37 member and an opposed said one of said upper frame member and said lower  
38 frame member.